SDS No.: ZT8R



Termin-8R Extreme Pressure Lubricant

SECTION 1. IDENTIFICATION

Product Identifier Termin-8R Extreme Pressure Lubricant

Part number ZT8R
Product Family Mixture

Recommended Use Corrosion inhibitor.

Restrictions on Use None known.

Supplier Identifier Spectra Products Inc., 41 Horner Avenue, Unit 2, Toronto, ON, M8Z 4X4, 416.252.2355

Emergency Phone No. Immediately contact your local poison control centre.

CANUTEC, +1.613.996.6666, for transportation emergencies.

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable aerosol - Category 2; Gas under pressure - Compressed gas

Label Elements





Warning

Flammable aerosol.

Pressurized container: may burst if heated.

Contains gas under pressure; may explode if heated.

Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Pressurized container: Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Store in a well-ventilated place.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Mineral oil	64742-65-0	45-70		
Petroleum gases, liquefied	68476-85-7	15-20		
Kerosine (petroleum), hydrodesulfurized	64742-81-0	7-13		
Zinc dinonylnaphthalenesulfonate	28016-00-4	1-5		
Calcium alkylnaphthalene sulfonate	57855-77-3	1-5		

Product Identifier: Termin-8R Extreme Pressure Lubricant - Ver. 1

Date of Preparation: January 27, 2016

Date of Last Revision: November 26, 2018 Page 01 of 07

Distillates (petroleum), hydrotreated light	64742-47-8	1-5	
Alcohol ethoxylate	84133-50-6	1-5	

Notes

Any concentration shown as a range is due to batch processing.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Get medical advice or attention if you feel unwell or are concerned.

Eve Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists, get medical advice or attention.

Ingestion

Get medical advice or attention if you feel unwell or are concerned.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam. Use water to keep non-leaking, fire-exposed containers cool.

Unsuitable Extinguishing Media

DO NOT use water or water-based extinguishing agents.

Specific Hazards Arising from the Product

Closed containers may rupture violently when heated releasing contents. Contains gas under pressure; may explode if heated. Flammable aerosol. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, resulting in a fire hazard. May travel a considerable distance to a source of ignition and flash back to a leak or open container.

Fumes and smoke.

Special Protective Equipment and Precautions for Fire-fighters

Evacuate area. Fight fire from a safe distance or a protected location.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, if ventilation is not sufficient. Remove or isolate incompatible materials as well as other hazardous materials.

Environmental Precautions

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Contain and soak up spill with absorbent that does not react with spilled product. Place used absorbent into suitable, covered, labelled containers for disposal.

Product Identifier: Termin-8R Extreme Pressure Lubricant - Ver. 1 SDS No.: ZT8R

Date of Preparation: January 27, 2016

Date of Last Revision: November 26, 2018 Page 02 of 07

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Do not puncture or incinerate container even when empty. Do not spray on an open flame or other ignition source. Do not pierce or burn container, even after use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated, out of direct sunlight and away from heat and ignition sources.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH®	TLV®	OSHA PEL		
Chemical Name	TWA	STEL [C]	TWA	Ceiling	
Distillates (petroleum), hydrotreated light	200 mg/m3 A3	Not established	Not established	Not established	

Appropriate Engineering Controls

Sufficient mechanical ventilation to maintain exposures below the TLV. Under normal conditions of use, general ventilation should be satisfactory. Local ventilation is recommended if the product is misted or used in a confined space or if the TLV is exceeded. Make up air should always be supplied to balance air exhausted. Provide eyewash in work area, if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Not required but it is good practice to wear safety glasses or chemical safety goggles.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

Respiratory Protection

Not normally required if product is used as directed.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance Red Aerosol.

Odour Characteristic

Odour Threshold Not available

pH Not applicable

Melting Point/Freezing Point Not available (melting); Not available (freezing)

Initial Boiling Point/Range Not available

Flash Point > 127 °C (closed cup)

Evaporation Rate Not available

Flammability (solid, gas) Flammable aerosol

Upper/Lower Flammability or

Explosive Limit

6.0% (upper); 1.0% (lower)

Vapour Pressure Not available

Vapour Density (air = 1) > 1.0 Relative Density (water = 1) 0.859

Solubility Not available in water

Product Identifier: Termin-8R Extreme Pressure Lubricant - Ver. 1 SDS No.: ZT8R

Date of Preparation: January 27, 2016

Date of Last Revision: November 26, 2018 Page 03 of 07

Partition Coefficient, Not available

n-Octanol/Water (Log Kow)

Auto-ignition Temperature 229 °C (Kerosine (petroleum), hydrodesulfurized)

Decomposition Temperature Not available

Viscosity 28.59 centistokes at 40°C (kinematic)

Other Information

VOC % 22.7

Flame projection > 45 cm < 100 cm **NFPA Classification** Aerosol, Level 1

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Stable at ambient temperatures and pressures.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials

Oxidizing agents (e.g. peroxides).

Hazardous Decomposition Products

Fumes and smoke may be generated.

SECTION 11. TOXICOLOGICAL INFORMATION

Information presented below is for the entire product, unless otherwise specified.

Likely Routes of Exposure

Inhalation:

Skin contact;

Eye contact;

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Calcium alkylnaphthalene sulfonate	> 18000 mg/m3 (rat) (1-hour exposure)	> 5000 mg/kg (rat)	> 20 mg/kg (rabbit)
Mineral oil	Not available	> 5000 mg/kg (rat)	> 5000 mg/kg (rabbit)
Kerosine (petroleum), hydrodesulfurized	> 5200 mg/m3 (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Alcohol ethoxylate	Not available	2100 mg/kg (rat)	Not available

Skin Corrosion/Irritation

There is limited evidence of mild irritation.

Serious Eye Damage/Irritation

There is limited evidence of mild irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause nose and throat irritation.

Product Identifier: Termin-8R Extreme Pressure Lubricant - Ver. 1 SDS No.: ZT8R

Date of Preparation: January 27, 2016

Date of Last Revision: November 26, 2018 Page 04 of 07

Skin Absorption

No information was located.

Ingestion

Ingestion can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located.

Respiratory and/or Skin Sensitization

Not known to be a respiratory sensitizer.

Not known to be a skin sensitizer.

Carcinogenicity

Chemical Name	ACGIH®	IARC	NTP	OSHA
Distillates (petroleum), hydrotreated light	A3	Group 3	Not Listed	Not Listed
Mineral oil	A4	Group 3	Not Listed	Not Listed
Petroleum gases, liquefied	Not Listed	Not Listed	Not Listed	Not Listed

Not known to cause cancer.

Key to Abbreviations

ACGIH® = American Conference of Governmental Industrial Hygienists. A3 = Animal carcinogen. A4 = Not classifiable as a human carcinogen.

IARC = International Agency for Research on Cancer. Group 3 = Not classifiable as to its carcinogenicity to humans. No information was located for: Development of Offspring, Sexual Function and Fertility, Effects on or via Lactation, Germ Cell Mutagenicity, Interactive Effects

SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Empty containers retain product residue. Follow label warnings even if container appears to be empty. Do not reuse empty containers. The container for this product can present explosion or fire hazards, even when emptied. Do not cut, puncture, or weld on or near this container. Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	UN1950	Aerosols	2.1	
US DOT	UN1950	Aerosols	2.1	
IMDG (Marine)	UN1950	Aerosols	2.1	
IATA (Air)	UN1950	Aerosols, flammable	2.1	

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Product Identifier: Termin-8R Extreme Pressure Lubricant - Ver. 1 SDS No.: ZT8R

Date of Preparation: January 27, 2016

Date of Last Revision: November 26, 2018 Page 05 of 07

Emergency Response 126 EmS F-D, S-U

Guide No.

Other Information ICAO/IATA PI Y203/203

Product may ship as LTD QTY if TDG, ICAO/IATA or IMDG Limited Quantity provisions are

met

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

CEPA - National Pollutant Release Inventory (NPRI)

(Distillates (petroleum), hydrotreated light) Part 5.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA: Not applicable.

SARA Title III - Section 302: Not applicable. SARA Title III - Section 313: Not applicable. California Proposition 65: Not applicable. Massachusetts Right To Know: Not applicable.

New Jersey Right To Know. (Petroleum gases, liquefied) Pennsylvania Right To Know. (Petroleum gases, liquefied)

SECTION 16. OTHER INFORMATION

NFPA Rating Health - 1 Flammability - 2 Instability - 0

Based on Kerosine (petroleum), hydrodesulfurized

SDS Prepared By Regulatory Compliance

Phone No. 905.847.0222

Date of Preparation January 27, 2016

Date of Last Revision November 26, 2018

Revision Indicators The following SDS content was changed on November 26, 2018:

SECTION 1. IDENTIFICATION; Emergency Phone No.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS; Ingredient Information;

Notes.

Key to Abbreviations ACGIH® = American Conference of Governmental Hygienists

CANUTEC = Canadian Transport Emergency Centre

CAS = Chemical Abstract Service

CCOHS = Canadian Centre for Occupational Health & Safety

CNS = Central nervous system

GESTIS = GESTIS Substance Database
HSDB® = Hazardous Substances Data Bank
IARC = International Agency for Research on Cancer
ICAO = International Civil Aviation Organization

IMDG = International Maritime Dangerous Goods Code

LC = Lethal concentration

LC = Lethal dose

NFPA = National Fire Protection Association

NTP = National Toxicology Program

OSHA = US Occupational Safety and Health Administration

Product Identifier: Termin-8R Extreme Pressure Lubricant - Ver. 1 SDS No.: ZT8R

Date of Preparation: January 27, 2016

Date of Last Revision: November 26, 2018 Page 06 of 07

PPM = Parts per million

RTECS® = Registry of Toxic Effects of Chemical Substances

STEL = Short term exposure limit

TDG = Transportation of Dangerous Goods Regulations (Canada)

TWA = Time weighted average

References Material safety data sheet from manufacturer.

CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS). HSDB® database. US National Library of Medicine. Available from Canadian Centre for

Occupational Health and Safety (CCOHS).

Registry of Toxic Effects of Chemical Substances (RTECS®) database. Accelrys, Inc. Available

from Canadian Centre for Occupational Health and Safety (CCOHS). ECHA - European Chemical Agency, Classification and Labelling Inventory

GESTIS Substance Database

OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2015.

Disclaimer The information contained herein is offered only as a guide to the use and handling of this

specific material and has been prepared in good faith. It is not intended to be all-inclusive, and the manner and conditions of use and handling may involve other and additional

considerations. No warranty of any kind is given or implied. Shrader Canada Limited will not be liable for any damages, losses, injuries or consequential damages which may result from the

use of or reliance on any information contained herein.

Product Identifier: Termin-8R Extreme Pressure Lubricant - Ver. 1

Date of Preparation: January 27, 2016

Date of Last Revision: November 26, 2018 Page 07 of 07

SDS No.: ZT8R

